

Bag Filter

AFE

1. Introduction

For a wide number of filtration applications bag filters are a simple, easy to use and economical choice. Within the edible oil industry bag filters are commonly used during several process steps. These AFE bag filter housings are excellent for use in the safety filtration edible oil at the end of crude oil or bleaching steps, for example.

But they are also suitable for polishing filtration of edible oil. The AFE bag filter housings are available for size 1 and size 2 filter bags and manufactured from stainless steel. The maximum temperature for these housings is 120 °C. The design temperature in combination with the PED category makes these housings an economical filter solution for edible oil applications.



2. Features

- Easy to use, good interior sealing and accessibility.
- Cover closing with hinged eye bolts and eye nuts (galvanised steel).
- Stainless steel bolts and nuts optional.
- Flat cover with handle.
- O-ring sealing: standard Buna-N. Other materials on request.
- Strong stainless steel metal mesh support basket for low flow resistance and maximum utilisation of entire surface area.
- Slightly conical support basket for easy filter bag removal.
- Liquid displacement cover: no liquid runs over the side when opening the filter.
- Liquid displacer units are available to further reduce the dead volume inside the filter bags.
- Perfect sealing between unfiltered liquid and filtered liquid is achieved by a spring-loaded hold-down device onto the filter bag and support basket. The filter bag seals with a felt-covered Snap-Collar ring or plastic seal which tightly fits into the support basket.
- Height-adjustable legs.

3. Standard specifications

Design pressure: 0 / 10 bar(g)
Design temperature: - 10 / 120 °C
Operating temperature: depending on the filter media and gaskets used

PED 2014/68/EU: article 4 paragraph 3


Maximum differential pressure

design: 4.0 bar
operating: 2.5 bar

4. Filter bags

Filtration Group supplies a wide range of filter bags in different materials, pore sizes, dimensions and models to fit in amafilter housings as well as those of other manufacturers.

For detailed information about amaFlow filter bags, please see respective Data Sheets.



Nozzle specification

N1 :	Inlet
N2 :	Outlet
N3 :	Vent (Rp ¼ - ISO7-1)

5. Dimensions

Size	Diameter [mm]	Standout [mm]	Height [mm]	Nozze height [mm]	Volume [dm ³]	Weight [kg]
	A	B	C	D		
90	219	156	max. 1020	max. 895	19	max. 21
180	219	Threaded: 156 Flanged: 210	max. 1370	max. 1245	34	max. 33

Dimensions are for reference only. Use dimensional drawing for installation purposes.

Subject to technical alteration without prior notice.

6. Ordering code

Example

AFE	180	T
Type	Size	Material
	90 = for bag size 1	No symbol = carbon steel
	180 = for bag size 2	T = 316Ti (1.4571)
		TY = 316Ti (1.4571) with stainless steel bolts and nuts

2F
Inlet/outlet
2 = Rp2 - ISO7-1

Size 180 only

2F = DN50 acc. EN1092/PN16
3F = DN80 acc. EN1092/PN16
ASME B16.5 150 lbs RF on request (FA)